



Moreland
COMPANY USA



Premium Underlayment

Moreland Company USA

1617 S. Tuttle Ave, Fl 3

Sarasota, FL 34239

(800) 397-7769



www.UltraplyXL.com



Wood is the only renewable and recyclable building material.

Wood is the answer!

The world market is committed to environmentally sound building materials. The Moreland Company USA is committed to sustainable forest management worldwide. The Moreland Company USA promotes efforts to achieve the fastest practical progress towards environmentally sound permanent forests internationally. Moreland Company USA encourages the use of wood products as an environmentally friendly and renewable resource, and is consistently finding beneficial ways to reduce wood waste and to utilize residues.

Moreland Company USA supports national and international efforts such as LEED and FSC that focus attention on the many threatening practices to the World's productive forests. Moreland Company USA requires suppliers to show evidence that they and their respective Governments are undertaking practical measures to implement the Lacey Act requirements. These are programs that work to achieve sustainable management of our plantation programs forest for future generations.

These criteria apply to all products Moreland Company USA offers. Using Moreland Company USA products creates value to the forest, an important and essential natural resource. This "value" provides the means for reforestation and sustainable forest management.

Moreland Company USA



...A Commitment to the Future



Reforestation Project



Seedlings

90 day seedlings



A new well maintained forest



Premium Underlayment

1/4" & 3/8" nominal thickness

UltraplyXL® Premium Underlayment

Lifetime Warranty

VINYL, CARPET, WOOD, CERAMIC, VCT, RUBBER, LAMINATE
& CORK FLOORING

UltraplyXL® underlayment plywood in all applications when handled and used as floor underlayment in accordance with these installation instructions is guaranteed for life:

- -Not to DELAMINATE
- -Not to have core voids & core laps that render this plywood un-useable as underlayment
- -Not to be the sole cause of the floor covering "yellowing"
- -Not to transfer wood colors to floor covering

Under this warranty and any and all implied warranties is expressly limited to, at the company's option:

- (A) Supplying replacement panels, or
- (B) Refunding the full purchase price of the panels, or
- (C) Replacing underlayment, adhesive and floor covering affected without charge,
- (D) Refunding the full cost (including installation cost) of the underlayment, adhesive and floor covering affected.

The Moreland Company USA has the highest quality of standards in the market. Environment and temperature should be noted to ensure acclimation. The finished floor covering should be installed immediately after UltraplyXL® Premium underlayment to prevent job sight influenced damage. Moreland Company USA is not responsible for faulty installation. No defective or damaged material is to be installed, and final inspection of each panel is the responsibility of the installer.

See UltraplyXL® brochure for full warranty details



- Lifetime Warranty
- 5 ply 1/4" & 7 ply 3/8" veneer core constructed
- 4x4 & 4x8 sizes are available in 1/4" and 3/8" sizes
- Scores & snaps with a knife for easy and fast installations
- Guaranteed against "yellowing"
- Whole piece face with no defects
- Solid Construction
- Marine Grade Glue
- Select hardwood construction
- Guaranteed not to have core voids or core laps that renders UltraplyXL® unusable as underlayment
- No Call backs



Installation Procedures

1/4”

Acclimation:

Condition UltraplyXL® Underlayment panels 24 to 48 hours to the room environment in which they will be installed.

- Install UltraplyXL® Premium Underlayment stamp side down before installing the finished floor.
- Install the long dimension of the panel perpendicular to the floor joists for maximum rigidity.
- Make sure UltraplyXL® Underlayment seams offset any sub floor panel seam by at least 6”.
- Stagger panels, ashlar fashion, so that four corners do not meet. Offset UltraplyXL® Underlayment joints by at least 16”.
- Leave a minimum 1/8” gap at walls.
- Lightly butt all panels, but do not force sheets into place.
- Fasten panels securely to a structurally sound, smooth clean and dry sub-floor with 18 gauge staples with chiseled ends & / or 12 gauge non-staining, galvanized ring groove shank nails.
- Make sure fasteners do not penetrate through the sub-floor or into the floor joists.
- Position fasteners in the field on 4” inch centers.
- Attach edge fasteners 1 1/2” apart and 3/8” from edge.
- Set fasteners flush or slightly below the panel surface.
- Fill all edge joints and other surface depressions with a PORTLAND BASED LATEX MODIFIED PATCH, and sand smooth. Make sure patch is FULLY DRY before installing the finished floor.



Installation Procedures

3/8”

Acclimation:

Condition UltraplyXL® Underlayment panels 24 to 48 hours to the room environment in which they will be installed.

- Install UltraplyXL® stamp side down before installing the finished floor.
- Install the long dimension of the panel perpendicular to the floor joists for maximum rigidity.
- Make sure UltraplyXL® Underlayment seams offset any sub-floor panel seam by at least 6”.
- Stagger panels, ashlar fashion, so that four corners do not meet. Offset Underlayment joints by at least 16”.
- Leave a minimum 1/8” gap at walls.
- Lightly butt all panels, but do not force sheets into place.
- Fasten panels securely to a structurally sound, smooth clean and dry sub-floor with 18g staples with chiseled ends &/or non-staining, 12g galvanized ring groove shank nails.
- Make sure fasteners do not penetrate through the sub-floor or into the floor joists.
- Position fasteners in the field on 4” inch centers.
- Attach edge fasteners 1 ½” apart and 3/8” from edge.
- Set fasteners flush or slightly below the panel surface.



- 2 Units of 4x4 and 4x8 UltraplyXL® Underlayment



- Example of our 4-way pallets, standard on both 4x4 and 4x8 units.



Packaging & Fulfillment

- Truckload Quantities
 - 32 Units of 4x8
 - 64 Units of 4x4
 - 80 piece units
 - Custom mixes & drop shipments available
 - 4x8 units weigh 1560 lbs.
 - 4x4 units weigh 775 lbs.
 - Each unit is 22 inches tall
- Shipped from:
 - Jersey City, NJ
 - Chicago, IL
 - Tacoma, WA
 - Los Angeles, CA
 - Oakland, CA
 - Dallas, TX
 - Flatbed
 - Van



Communication Strategies

- In-house Experienced and dedicated sales telemarketing team
- Product hand samples
- Warranty brochures
- World wide web access
- Advertisements in major trade magazines
- Major trade show attendance
- Moreland Company USA is the Pioneer in Premium Plywood Underlayment for the USA with over 20 years of proven performance.
- UltraplyXL® Brand of 4'x4' and 4' x 8' continues to be the brand of choice in the industry.



Moreland
COMPANY USA

Visit our web site for:

- All staff email address's
- Lifetime Transferable
Warranty residential and
commercial
- Up to date installation
instructions

www.UltrapplyXL.com

