



Wood is the Answer

Wood is the only renewable and recyclable building material! The world market is dedicated to providing environmentally sound building materials. The Moreland Company USA is committed to sustainable forest management worldwide. We promote efforts to achieve the fastest practical progress towards environmentally sound permanent forests internationally. Moreland Company USA encourages the use of wood products as an acceptable and renewable resource and is consistently finding beneficial ways to reduce wood waste and to utilize residues.



TACK STRIP



Please look for our FSC certified Labeled products



1617 S. Tuttle Ave, Flr 3  
Sarasota, FL 34239  
800-397-7769



www.ultraplyxl.com



Vinyl, Carpet,  
Tile & Wood Flooring



### Warranty

UltraplyXL® Underlayment Plywood will hold floor coverings firmly when the floor covering is adhered in accordance with the floor covering and adhesive manufacturer's instructions.

UltraplyXL® Underlayment Plywood in all applications when handled and used as floor underlayment in accordance with these installation instructions is guaranteed for LIFE!

- Not to delaminate
- Not to have core voids or core laps that render it unusable
- Not to be the sole cause of "yellowing"
- Not to transfer wood colors to the floor covering

Under this warranty any and all implied warranties are expressly limited to, at the company's option:

- Supplying replacement panels, or
- Refunding the full purchase price of the panels, or
- Replacing underlayment, adhesive and floor covering affected without charge, or
- Refunding the full cost (including installation cost) of the underlayment, adhesive and floor covering affected.

In the event of yellowing an independent lab will be employed to determine the cause of the yellowing, the "at fault" material supplier will be liable for all costs incurred due to the problem. In no event shall the company's liability for any claim exceed the wholesale cost (including installation cost) of the underlayment, adhesives, and floor covering affected.

This warranty does not cover damages due to improper installation of floor covering material. In addition, tears or ruptures to the floor surface, standing water, fire, floods, natural disasters or faults in the plumbing which affects the performance of the flooring system are not covered.

This warranty is non-transferable and covers only the original use in residential applications. All warranties are good for one year in commercial applications.

Liability shall expressly exclude any other liability to the purchaser or any other person for direct, indirect or consequential damages.

*You must notify Moreland Co., USA within 30 days after discovery of product found to be defective under this warranty. An authorized representative from Moreland Co. must be given the opportunity for 30 days after such notice to inspect floor prior to any alterations, change or repair. In any case where Moreland Co. is not notified before any alterations, change or repair is made to the floor, Moreland Co. is released from any liability on the claims.*

**All claims must be submitted in writing within 30 days after the discovery of any defect to: Moreland Fax #: 941-953-5180**



www.morelandcompany.com



### Installation Instructions

Acclimation: Condition UltraplyXL® Underlayment panels 24 to 48 hours to the room environment in which they will be installed.


- Install UltraplyXL® stamp side down before installing the finished floor.
- Install the long dimension of the panel perpendicular to the floor joists for maximum rigidity.
- Make sure UltraplyXL® Underlayment seams offset any sub-floor panel seam by at least 6".
- Stagger panels, ashlar fashion, so that four corners do not meet. Offset Underlayment joints by at least 16".
- Leave a minimum 1/8" gap at walls.
- Lightly butt all panels, but do not force sheets into place.
- Fasten panels securely to a structurally sound, smooth clean and dry sub-floor with divergent staples with chiseled ends &/or non-staining, galvanized ring groove shank nails.
- Make sure fasteners do not penetrate through the sub-floor or into the floor joists.
- Position fasteners in the field on 4" inch centers.
- Attach edge fasteners 1 1/2" apart and 3/8" from edge.
- Set fasteners flush or slightly below the panel surface.

**Fill all edge joints and other surface depressions with PORTLAND BASED LATEX MODIFIED PATCH, and sand smooth. Make sure patch is FULLY DRY before installing the finished floor.**

\* Notes & Acceptions:


**The Moreland Company has the highest standards of quality in the market. Environment and temperature should be noted to ensure acclimation. The finished floor should be installed immediately after UltraplyXL® Premium Underlayment to prevent job site influenced damage. Moreland Company is not responsible for faulty installation. No defective material is to be installed. Final inspection of each panel is the responsibility of the installer.**

Panel Placement



Ashlar Fashion at least 16"

Staple Pattern



Butterfly Pattern 4" on Center

Designed by Installers for Installers!



- Lifetime Warranty
- 5 ply veneer core constructed
- 4x8 size available
- 1/4 inch nominal thickness
- Scores and snaps with a knife for easy installation
- Guaranteed against "yellowing"
- Whole piece face with no defects
- Solid construction
- Marine grade glue
- Select hardwood construction
- Guaranteed not to delaminate
- Guaranteed not to have core voids or core laps that renders UltraplyXL® unusable as underlayment
- No call backs!



www.morelandcompany.com